

CPVC/PVC System



PGS-300 Grooved End Fittings


[Download publication 33.03](#) for complete information

- Exclusively for use on CPVC/PVC pipe featuring Victaulic's proprietary PGS-300 groove profile
- Sizes from 2–12" | DN50–DN300
- Refer to the publication for maximum pressure ratings and temperature reduction factors
- Regional availability, contact [Victaulic](#) for details


Certifications/Listings:




[Download publication 02.06](#) for ANSI/NSF Potable Water Approvals/Listings




No. 350
90° Elbow




No. 351
45° Elbow




No. 352
Tee




No. 353
Reducing Tee
(Groove × Groove
× Groove)



No. 354
Reducing Tee
(Groove × Groove
× Socket)



No. 359F
Flange Adapter
(Groove × Flange)



No. 361
Reducing Adapter
(Groove × Socket)



PGS-300 Grooved End Expansion Joint

STYLE 355

[Download publication 33.05](#) for complete information

- Exclusively for use on CPVC/PVC pipe featuring Victaulic's proprietary PGS-300 groove profile
- Provides increased axial expansion and full axial movement at each joint
- Combination of Style 357 rigid couplings and short grooved nipples, joined in tandem to provide increased expansion
- Sizes from 2–12" | DN50–DN300
- Refer to the publication for maximum pressure ratings and temperature reduction factors
- Regional availability, contact [Victaulic](#) for details

OGS

AGS

VBSP

Hole Cut

Plain End

Stainless Steel

Potable Water

Shouldered Steel

Ductile Iron

High Performance

Hydronic Balancing

HDPE

Aquamine™ PVC

CPVC/PVC

Specialty

Tools

Gaskets, Seals and O-Rings

Design Data

Reference Guide