



Duplex Lightweight Flexible Coupling

STYLE 475DX

[Download publication 17.34](#) for complete information

- Unique coupling design permits assembly by removing one nut/bolt and swinging the housing over the gasket
- Designed for use with fittings and valves featuring Victaulic® Original Groove System (OGS) grooved ends for fast installation
- Sizes from 1–4" | DN25–DN100
- Pressures up to 500 psi | 3447 kPa | 34 bar
- Optional super duplex stainless steel housing
- For the Type 316 stainless steel coupling, [download publication 17.14](#) for Style 475



Type 316 Vic-Flange Adapter

STYLE 441

[Download publication 17.27](#) for complete information

- ANSI Class 150
- Constructed from Grade CF8M stainless steel, making it ideal for externally corrosive environments
- Sizes from 2–6" | DN50–DN150
- Pressures up to 275 psi | 1896 kPa | 19 bar
- Available Flange Adapter Nipples:
No. 445F Flat Face Flange Adapter Nipple
No. 445R Raised Face Flange Adapter Nipple
No. 441N Flange Adapter Nipple (For EMEAI only)



Stainless Steel Mechanical-T Bolted Branch Outlet

STYLE 422

[Download publication 17.02](#) for complete information

- Provides a direct Victaulic Original Groove System (OGS) grooved or female threaded branch connection at any location where a hole can be cut in the pipe
- A pressure responsive gasket provides the seal
- Also suitable for use with HDPE pipe
- Sizes from 2–10" | DN50–DN250
- Pressures up to 300 psi | 2068 kPa | 21 bar

Certifications/Listings:



[Download publication 02.06](#) for ANSI/NSF Potable Water Approvals/Listings

Stainless Steel System



Stainless Steel Schedule 10S Fittings

[Download publication 17.16](#) for complete information

- Grooved ends eliminate pipe end preparation for the fittings
- Designed for use with couplings featuring Victaulic® Original Groove System (OGS) grooved ends for fast installation
- Sizes from ¾ – 12" | DN20 – DN300
- Available in Type 304L or 316L
- [Download publication 17.27](#) for stainless steel flange options

Certifications/Listings:



[Download publication 02.06](#) for ANSI/NSF Potable Water Approvals/Listings



No. 410 SS
90° Elbow




No. 411 SS
45° Elbow




No. 412 SS
22½° Elbow




No. 413 SS
11¼° Elbow




No. 420 SS
Tee




No. 425 SS
Grooved Branch
Reducing Tee



No. 430 SS
45° Lateral



No. 433 SS
True Wye



No. 435 SS
Cross



No. 441N
Flanged
Adapter Nipple
(EMEA-I Only)



No. 442 SS
Adapter Nipple
(Groove ×
Bevel)



No. 443 SS
Adapter Nipple
(Groove ×
Groove)



No. 445F
Flat Face
Flanged
Adapter Nipple



No. 445R
Raised Face
Flanged
Adapter Nipple



No. 450 SS
Concentric
Reducer



No. 451 SS
Eccentric
Reducer



No. 460 SS
Cap



Stainless Steel Schedule 40S Fittings

[Download publication 17.16](#) for complete information

- Grooved ends eliminate pipe end preparation for the fittings
- Designed for use with couplings featuring Victaulic® Original Groove System (OGS) grooved ends for fast installation
- Sizes from ¾ – 12" | DN20 – DN300
- Available in Type 304L or 316L
- Designed for higher pressure systems
- [Download publication 17.27](#) for stainless steel flange options

Certifications/Listings:



[Download publication 02.06](#) for ANSI/NSF Potable Water Approvals/Listings



No. 410HSS
90° Elbow




No. 411HSS
45° Elbow




No. 412HSS
22½° Elbow




No. 413HSS
11¼° Elbow




No. 420HSS
Tee




No. 425HSS
Grooved Branch Reducing Tee



No. 430HSS
45° Lateral



No. 433HSS
True Wye



No. 435HSS
Cross



No. 440HSS
Adapter Nipple
(Groove x Thread)



No. 441N
Flanged Adapter Nipple
(EMEA-I Only)



No. 442HSS
Adapter Nipple
(Groove x Bevel)



No. 443HSS
Adapter Nipple
(Groove x Groove)



No. 445F
Flat Face Flanged Adapter Nipple



No. 445R
Raised Face Flanged Adapter Nipple



No. 450HSS
Concentric Reducer



No. 451HSS
Eccentric Reducer



No. 460HSS
Cap